



ASH LED Panel Series



Ideal for Offices and Commercial Buildings

L70 Rated to 30,000 hours.

120 Degree Beam Angle

Up to 3255 Lumens

5 Year Warranty

Osram Driver

The Di-Astrum ASH LED Panel is an ideal solution to replace existing recessed ceiling grid fittings in Office, Commercial, Retail, and Education applications. These back lit, lightweight, LED fittings are available in 595 x 595 and are suitable for use in existing T Bar 600 x 600 ceiling grid systems. They are constructed of extruded Aluminium Powder Coated Chassis and PMMA diffuser. These products are offered with a 5 Year Warranty.

Features

- 5 Year Warranty
- L70 to 30,000 Hrs
- IP20
- 120 Degree Beam Angle
- RoHS Compliant
- Back Lit
- Osram Driver

Benefits

- Up To 50% Energy Savings
- Zero Maintenance
- Improved Light Quality

Typical Applications

- Offices
- Retail Outlets
- Reception Areas
- Schools
- Hospitals
- Corridors
- Commercial Buildings
- Colleges
- Universities

Electrical Information

Nominal Wattage	39W
Drive Current	900mA
Operating Temp	-20 °C to +40 °C
Power Factor	> 0.95
THD	< 20%
Input Voltage	110-240 VAC
CRI	> 80
CCT	5000K

Mechanical Information

Sizes	595 x 595
Weight	5.2 KG
Mounting	Recessed
IP Rating	IP20
Housing	Power Coated Steel
Diffuser	PMMA

Ordering Information

Part Number	Wattage	Lumen	Dimensions
DA-ASH-6060-39W-50K-S	39W	3380	595 x 595 x 72
DA-ASH-6060-39W-50K-T	39W	3490	595 x 595 x 72

Additional Options

Emergency	-EM Suffix In Above Part Codes
Switch Dimming	-SDIM Suffix In Above Part Codes
DALI	-DALI Suffix In Above Part Codes
Microwave Sensor	-MIC Suffix In Above Part Codes