



Apricot LED Panel Series



Ideal for Offices and Corridors.

L70 Rated to 30,000 hours.

120 Degree Beam Angle

Up to 6400 Lumens

5 Year Warranty

Osram Driver (X2 in 1195 x 595 Fixture)

The Di-Astrum Apricot LED Panel is an ideal solution to replace existing recessed ceiling grid fittings in office, commercial, and hospital applications. These back lit, lightweight, LED fittings are available in 595 x 595 and 1195 x 595 sizes and are suitable for use in existing T Bar 600 x 600 ceiling grid systems. They are constructed of extruded Aluminium Powder Coated Chassis and PMMA diffuser. These products are offered with a 5 Year Warranty.

Features

- 5 Year Warranty
- L70 to 30,000 Hrs
- IP20
- 120 Degree Beam Angle
- RoHS Compliant
- Back Lit

Benefits

- Up To 50% Energy Savings
- Zero Maintenance
- Improved Light Quality

Typical Applications

- Offices
- Schools
- Hospitals
- Corridors
- Commercial Buildings
- Colleges
- Universities

Electrical Information

Nominal Wattage	36 - 70W
Drive Current	850mA
Operating Temp	-20 °C to +35 °C
Power Factor	> 0.95
THD	< 20%
Input Voltage	110-240 VAC
CRI	> 80
CCT	5000K

Mechanical Information

Sizes	595 x 595, 1195 x 595
Weight	5.2 KG
Mounting	Recessed
IP Rating	IP20
Housing	Power Coated Steel
Diffuser	PMMA

Ordering Information

Part Number	Wattage	Lumen	Dimensions
DA-APR-6060-40W-50K	36W	3450	595 x 595 x 55
DA-APR-1260-70W-50K	70W	6400	1195 x 595 x 55

Additional Options

Emergency	-EM Suffix In Above Part Codes
Switch Dimming	-SDIM Suffix In Above Part Codes
DALI	-DALI Suffix In Above Part Codes
Microwave Sensor	-MIC Suffix In Above Part Codes