



Openspace LED Area Flood



- Ideal for Area Flood Lighting
- L70 Rated to 50,000 hours.
- IP65 Water & Dustproof
- IK09 Impact Resistant
- Fully CE Certified

Features

- IP65
- IK09
- CE Certified
- L70 to 50,000 Hrs
- 5 Year Warranty
- Modular Design
- Non Corrosive
- 90 Degree Beam Angle
- PMMA Lens Optic
- RoHS Compliant

Benefits

- Up To 66% Energy Savings
- Zero Maintenance
- Improved Light Quality

Typical Applications

- High Mast
- Flood Lighting
- Open Area Lighting

The Di-Astrum Openspace LED Area Flood is designed to replace existing HID solutions in High Mast, Open Area, and Flood Lighting Applications. The modular LED light bars allow for variations in wattage and lumen output allowing this product to be scaled depending on the existing units being replaced. Utilizing Epistar LED chips and Meanwell Driver, and housed in a Die-Cast Aluminium Chassis, this series is provided with a 5 Year UK Backed Warranty.

Electrical Information

Nominal Wattage	60 - 180W
Drive Current	850mA
Operating Temp	-20 °C to +50 °C
Power Factor	> 0.95
Input Voltage	110-277 VAC
CRI	70
CCT	6500K

Mechanical Information

Size	See Table
Weight	2.4 – 5.4 KG
Mounting	Swivel Bracket
IP Rating	IP65
IK Rating	IK09
Housing	Die-Cast Aluminium
Diffuser	PMMA

Ordering Information

Part Number	Wattage	Lumen Output	Dimensions
DA-OPN-HMAF-80W-6500K	60W	5,750	298 x 230 x 145mm
DA-OPN-HMAF -40W-6500K	90W	8,800	298 x 340 x 145mm
DA-OPN- HMAF-120W-6500K	120W	11,600	298 x 430 x 145mm
DA-OPN- HMAF-180W-6500K	180W	17,200	347 x 596 x 154mm